

View Online at <https://aerobasegroup.com/nsn/5930-00-412-1071>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Shaft Diameter:

0.500 inches single actuator

Shaft Length:

0.750 inches single actuator

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Metallic inclosure

Thready Qty Per Inch (tpi):

18 single mounting facility

Thread Size:

0.312 inches single mounting facility

Contact Voltage Rating In Volts:

575.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, fluted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

68.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Special Features:

10 degrees lever travel to trip switch, two 1/2-14 thd @conduit entrances on top

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0