

View Online at <https://aerobasegroup.com/nsn/5930-00-412-1073>

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

6.230 inches

Overall Height:

2.710 inches

Overall Width:

4.750 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

3.100 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.813 inches

Mounting Method:

Bracket

Features Provided:

Automatic reset

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

400.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+50.00/+250.00 actuation point pounds per square inch gage and +35.00/+235.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal deactuation point hex nut and internal actuation point hex nut

Contact Voltage Rating In Volts:

250.0 ac at sea level first voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0