NSN 5930-00-412-1114



Lever Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-412-1114 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.468 inches **Body Length:** 2.375 inches **Body Width:** 0.875 inches **Body Height:** 1.000 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.687 inches **Actuator Style:** Round **Actuator Diameter:** 0.375 inches **Actuator Height:** 1.000 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained **Actuator Position-locking Relationship:** Up position locked in and down position no locking action **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 110.0 ac **Inclosure Type:** Uninclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): **Pile-up Contact Form Arrangement:** 4a single position **Thread Size:** 0.099 inches **Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive ac

Precious Material And Location:

Contacts palladium

Thread Series Designator:

Unc

NSN 5930-00-412-1114

Lever Switch - Page 2 of 2



Terminal Type	And	Quantity:
---------------	-----	-----------

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0