

View Online at <https://aerobasegroup.com/nsn/5930-00-412-1454>

Thread Class:

2a all threaded stud

Thread Length:

0.375 inches all threaded stud

Hazardous Locations/environmental Protection:

Driptight

Overall Height:

0.750 inches

Body Height:

0.375 inches

Overall Diameter:

0.625 inches

Tempurature Sensing Element Type:

Internal sensor

Mounting Method:

Threaded stud

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded stud

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

130.00 actuation point degrees celsius and 120.00 deactuation point degrees celsius and 10.00 differential point degrees celsius

Contact Voltage Rating In Volts:

125.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Thread Series Designator:

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0