NSN 5930-00-412-1583

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-412-1583

Body Style:
Bushing/hole mounted
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
2.402 inches
Overall Width:
0.687 inches
Bushing Length:
0.610 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
1.030 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.942 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.180 inches
Maximum Voltage Rating In Volts:
250.0 ac
End Application:
Los angeles/sturgeon
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:

0.469 inches

NSN 5930-00-412-1583

Sensitive Switch - Page 2 of 2



Nonpile-up Contact Arrangement:
1 two circuit, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 16.0 ounces and 26.0 ounces
Actuator Movement:
0.140 overtravel inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive ac
Special Features:
One terminal common
Thread Series Designator:
Uns
Terminal Type And Quantity:
5 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

Fiig: A053a0