NSN 5930-00-412-4260

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-412-4260

Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.356 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.092 inches
Actuator Height:
0.050 inches
Actuator Free Position Height:
0.375 inches
Maximum Voltage Rating In Volts:
30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
Between 3.0 ounces and 5.0 ounces
Actuator Movement:
Between 0.020 pretravel inches and 0.003 overtravel inches and 0.001 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-00-412-4260 Sensitive Switch - Page 2 of 2



Fiig:

A053a0