NSN 5930-00-412-4288

Toggle Switch - Page 1 of 2

0.250 inches



View Online at https://aerobasegroup.com/nsn/5930-00-412-4288

| Body Style: | | | | | |
|--|--|--|--|--|--|
| Bushing mount | | | | | |
| Hazardous Locations/environmental Protection: | | | | | |
| Dustproof | | | | | |
| Overall Length: | | | | | |
| 0.843 inches | | | | | |
| Overall Height: | | | | | |
| 1.323 inches | | | | | |
| Overall Width: | | | | | |
| 0.500 inches | | | | | |
| Bushing Length: | | | | | |
| 0.352 inches | | | | | |
| Body Length: | | | | | |
| 0.843 inches | | | | | |
| Body Width: | | | | | |
| 0.500 inches | | | | | |
| Body Height: | | | | | |
| 0.475 inches | | | | | |
| Case Material: | | | | | |
| Metal | | | | | |
| Switch Actuator Quantity: | | | | | |
| 1 | | | | | |
| Actuator Style: | | | | | |
| Round | | | | | |
| Actuator Diameter: | | | | | |
| 0.115 inches | | | | | |
| Actuator Height: | | | | | |
| 0.400 inches | | | | | |
| Actuator Position-action Relationship: | | | | | |
| Up position maintained and down position maintained and center position maintained | | | | | |
| Maximum Voltage Rating In Volts: | | | | | |
| 115.0 ac and 24.0 dc | | | | | |
| Inclosure Type: | | | | | |
| Fully enclosed | | | | | |
| Mounting Method: | | | | | |
| Threaded bushing | | | | | |
| Features Provided: | | | | | |
| Actuator seal | | | | | |
| Thready Qty Per Inch (tpi): | | | | | |
| 40 | | | | | |
| Thread Size: | | | | | |

NSN 5930-00-412-4288

Toggle Switch - Page 2 of 2



| ١ | lon | au-elic | Contact | Arrangem | ent: |
|---|-----|---------|---------|----------|------|
| | | | | | |

4 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts and terminals silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0