

View Online at <https://aerobasegroup.com/nsn/5930-00-413-1014>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

1.940 inches

**Overall Height:**

1.560 inches

**Overall Width:**

1.380 inches

**First Flat Length:**

0.440 inches single actuator

**Flat Height:**

0.221 inches single actuator

**Shaft Diameter:**

0.251 inches single actuator

**Shaft Length:**

1.060 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 3:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

11 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

300.0 ac at sea level

**Shaft Flat/slot Angular Location:**

120.0 degrees from nonturn device single actuator

**Rotor Through Connection Quantity:**

1 single section

**Switch Actuator Indexing Position Quantity:**

11 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0