

View Online at <https://aerobasegroup.com/nsn/5930-00-415-1741>

Thread Class:

3a single pressure connection

Thread Length:

0.290 inches single pressure connection

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

2.250 inches

Body Length:

1.530 inches

Overall Diameter:

0.750 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 186.0 degrees fahrenheit

Mounting Method:

Clamp

Thready Qty Per Inch (tpi):

24 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.3125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

7500.00 pounds per square inch

Terminal Type:

Wire lead

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

2000.00 actuation point pounds per square inch gage and 300.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

10.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiq:

A048b0