

View Online at <https://aerobasegroup.com/nsn/5930-00-415-1908>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Explosion proof

Bushing Length:

Between 0.458 inches and 0.478 inches

Body Length:

0.562 inches

Body Width:

0.354 inches

Body Height:

0.425 inches

Actuator Style:

Rectangular

Actuator Height:

0.875 inches

Actuator Width:

0.300 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

125.0 ac and 50.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0