## NSN 5930-00-415-2791

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-415-2791

Thread Length:

0.312 inches single mounting facility

**Overall Length:** 

2.126 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

**Shaft Diameter:** 

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:** 

0.494 inches single actuator

**Overall Diameter:** 

1.297 inches

**Nonturn Device Radius:** 

0.531 inches at 3: 00 o'clock

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Operating Tempurature Range:** 

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section rear

**Throw Quantity:** 

10 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Shaft Flat/slot Angular Location:** 

135.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:** 

10 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section rear

# NSN 5930-00-415-2791

Rotary Switch - Page 2 of 2



Switch	Actuator	<b>Positioning</b>	Increment:

30.0 degrees single actuator

### **Detent Rotational Torque Range:**

+1.000/+8.000 inch-pounds single actuator

#### **Switch Actuator Stop Device Type:**

Fixed stop single actuator

#### **Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

#### **Style Designator:**

Circular wafer, bushing mount

#### **Test Data Document:**

81349-mil-s-3786/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A052b0