

View Online at <https://aerobasegroup.com/nsn/5930-00-416-9201>

Thread Length:

0.440 inches single mounting facility

Overall Length:

1.790 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.205 inches single actuator and 0.215 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.252 inches single actuator

Shaft Length:

0.380 inches single actuator

Overall Diameter:

1.100 inches

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 single section front

Throw Quantity:

3 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

90.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

1 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

28.0 amperes resistive load dc at sea level and 28.0 amperes inductive load dc at sea level

Special Features:

8.0 inch-ounces 5th shaft

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0