

View Online at <https://aerobasegroup.com/nsn/5930-00-416-9201>

**Thread Length:**

0.440 inches single mounting facility

**Overall Length:**

1.790 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.205 inches single actuator and 0.215 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.252 inches single actuator

**Shaft Length:**

0.380 inches single actuator

**Overall Diameter:**

1.100 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Slotted bushing at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

4 single section front

**Throw Quantity:**

3 single section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

90.0 degrees from contact position 1 single actuator

**Switch Actuator Indexing Position Quantity:**

1 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section front

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

28.0 amperes resistive load dc at sea level and 28.0 amperes inductive load dc at sea level

**Special Features:**

8.0 inch-ounces 5th shaft

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0