

View Online at <https://aerobasegroup.com/nsn/5930-00-417-3819>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Shock proof

**Body Diameter:**

1.030 inches

**Bushing Length:**

Between 0.970 inches and 1.030 inches

**Body Length:**

1.100 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

Between 1.751 inches and 1.810 inches

**Actuator Roller Diameter:**

Between 0.485 inches and 0.515 inches

**Actuator Roller Width:**

Between 0.105 inches and 0.135 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

80.0 ounces

**Switch Actuating Force:**

Between 96.0 ounces and 192.0 ounces

**Actuator Movement:**

Between 0.070 pretravel inches and 0.250 overtravel inches and 0.035 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes lamp dc

**Test Data Document:**

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0