NSN 5930-00-417-7299

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-417-7299

Thread Class:

2a single mounting facility

Thread Length:

 $0.360 \ \text{inches} \ \text{single} \ \text{mounting} \ \text{facility} \ \text{and} \ 0.390 \ \text{inches} \ \ \text{single} \ \text{mounting} \ \text{facility}$

Overall Length:

Between 2.562 inches and 2.626 inches

Overall Height:

1.766 inches

Overall Width:

1.766 inches

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.970 inches single actuator

Individual Section Quantity:

1

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

12 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

NSN 5930-00-417-7299

Rotary Switch - Page 2 of 2



Special Features:

Selected item drawing

Style Designator:

Tap, square frame

Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0