

View Online at <https://aerobasegroup.com/nsn/5930-00-417-7416>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.281 inches single mounting facility

**Overall Length:**

2.031 inches

**Overall Height:**

1.125 inches

**Overall Width:**

1.125 inches

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

1.062 inches single actuator and 1.124 inches single actuator

**Nonturn Device Radius:**

0.562 inches at 12: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 12: 00 o'clock

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 single section rear

**Throw Quantity:**

4 single section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

2 single section

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+0.300/+3.700 inch-pounds single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level

**Style Designator:**

Square wafer, panel mount

**Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0