NSN 5930-00-419-0222

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-419-0222

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Industrial use
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
1.130 inches
Housing Length:
3.700 inches
Housing Width:
1.570 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.310 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.190 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
72.0 inch-ounces
Actuator Movement:
Between 23.0 pretravel degrees and 27.0 overtravel degrees and 16.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive ac
Terminal Type And Quantity:
8 screw
Shelf Life:
N/a

NSN 5930-00-419-0222

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0