## NSN 5930-00-419-3932

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted



View Online at https://aerobasegroup.com/nsn/5930-00-419-3932

Overall Length:
1.880 inches
Overall Height:
2.680 inches
Overall Width:
0.750 inches
Body Length:
Between 1.440 inches and 1.560 inches
Body Width:
0.560 inches
Body Height:
Between 2.620 inches and 2.740 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.156 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.687 inches
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.380 inches
Actuator Free Position Height:
0.380 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Uninclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
25.0 ounces
Switch Actuating Force:
144.0 ounces
Actuator Movement:
0.120 pretrayel inches, and 0.630 quertrayel inches, and 0.250 differential inches

## NSN 5930-00-419-3932

Sensitive Switch - Page 2 of 2



Contact	I oad	Current	Rating	Δt	Maximum	Rated	Voltage:
Contact	Luau	Current	Naumy	$\neg$	WIGNIIII	Nateu	VOILAGE.

15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:** 

8 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0