NSN 5930-00-419-3968

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-419-3968

Thread Length: 0.375 inches single mounting facility **Overall Length:** 1.860 inches **Overall Height:** 1.250 inches **Overall Width:** 1.000 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.375 inches single actuator **Nonturn Device Radius:** 0.375 inches at 3: 00 o'clock **Individual Section Quantity: Nonturn Device Type:** Tab at 3: 00 o'clock **Operating Tempurature Range:** -65.0/+125.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 6 each section front **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 12 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

NSN 5930-00-419-3968

Rotary Switch - Page 2 of 2



Detent	Rotational	Torque	Range:
Dotonic	· totationai	. 0. 940	··ugc.

+20.000/+40.000 inch-ounces single actuator

Contact Load Current Rating:

350.0 milliamperes resistive load dc at sea level and 100.0 milliamperes inductive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0