

View Online at <https://aerobasegroup.com/nsn/5930-00-419-5132>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.307 inches single mounting facility and 0.317 inches single mounting facility

**Overall Length:**

Between 1.656 inches and 1.720 inches

**Overall Height:**

Between 0.995 inches and 1.005 inches

**Overall Width:**

Between 0.932 inches and 0.942 inches

**First Flat Length:**

0.297 inches single actuator and 0.329 inches single actuator

**Flat Height:**

0.091 inches single actuator and 0.095 inches single actuator

**Shaft Diameter:**

0.123 inches single actuator and 0.125 inches single actuator

**Shaft Length:**

0.656 inches single actuator and 0.720 inches single actuator

**Nonturn Device Radius:**

0.375 inches at 3:00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

135.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes 2nd section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+7.000/+9.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0