# NSN 5930-00-419-5205



Sensitive Switch - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5930-00-419-5205 **Body Style:** Hole mounted Center To Center Distance Between Mounting Facilities Parallel To Length: Between 0.870 inches and 0.880 inches **Body Length:** 1.094 inches **Body Width:** 0.406 inches **Body Height:** 0.625 inches **Unthreaded Mounting Hole Diameter:** Between 0.109 inches and 0.119 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.401 inches and 0.411 inches **Actuator Length:** Between 1.254 inches and 1.316 inches **Actuator Style:** Leaf **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **Inclosure Type:** 

Fully enclosed

## **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

## **Switch Release Force:**

1.0 ounces

# **Switch Actuating Force:**

8.0 ounces

#### **Actuator Movement:**

Between 0.125 pretravel inches and 0.080 overtravel inches and 0.050 differential inches

## **Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

## **Terminal Type And Quantity:**

3 quick disconnect, male

Shelf Life:

N/a

**Unit Of Measure:** 

## **Demilitarization:**

No

## Fiig:

A053a0