

View Online at <https://aerobasegroup.com/nsn/5930-00-419-7223>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.279 inches and 0.283 inches

**Body Length:**

0.510 inches

**Body Width:**

0.200 inches

**Body Height:**

0.350 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.090 inches and 0.093 inches

**Actuator Height:**

Between 0.095 inches and 0.110 inches

**Actuator Free Position Height:**

Between 0.340 inches and 0.375 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

1.5 ounces

**Switch Actuating Force:**

8.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

8.000 amperes resistive dc and 4.000 amperes inductive dc and 2.000 amperes lamp dc

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0