

View Online at <https://aerobasegroup.com/nsn/5930-00-419-7812>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.092 inches

Actuator Height:

0.043 inches

Actuator Free Position Height:

0.363 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

0.370 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

An/gyq-1

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

12.0 grams

Switch Actuating Force:

340.2 grams

Actuator Movement:

0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0