NSN 5930-00-419-7812

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-419-7812

View Online at https://aerobasegroup.com/nsn/5930-00-419-7812
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Switch Actuator Quantity:
1
Actuator Style:
Round
Actuator Diameter:
0.092 inches
Actuator Height:
0.043 inches
Actuator Free Position Height:
0.363 inches
Actuator Adapter Style:
Pushbutton
Adapter Bushing Length:
0.370 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
End Application:
An/gyq-1
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
40
Thread Size:
0.250 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit

12.0 grams

Switch Release Force:

NSN 5930-00-419-7812 Sensitive Switch - Page 2 of 2



Switch Actuating Force:
340.2 grams
-
Actuator Movement:
0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0