

View Online at <https://aerobasegroup.com/nsn/5930-00-420-0804>

Overall Length:

6.730 inches

Overall Height:

2.710 inches

Overall Width:

4.750 inches

Unthreaded Mounting Hole Diameter:

0.265 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

3.100 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

6.0 amperes resistive load third voltage and 5.0 amperes inductive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+20.00/+100.00 actuation point pounds per square inch and +14.00/+94.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point serrated nut and internal deactuation point serrated nut

Contact Stimulus Rating:

6.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

50.0 first voltage and 60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0