# NSN 5930-00-420-7433

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-420-7433

# Thread Class:

2b single mounting facility

# Hazardous Locations/environmental Protection:

Shock proof and vibration proof

# **Overall Length:**

4.938 inches

## **Overall Height:**

2.531 inches

## **Overall Width:**

2.531 inches

# Individual Section Quantity:

5

### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

### **Mounting Method:**

### Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

## Thready Qty Per Inch (tpi):

20 single mounting facility

## Thread Size:

0.250 inches single mounting facility

## **Contact Voltage Rating In Volts:**

500.0 ac at sea level

#### Switch Actuator Momentary Position:

Counterclockwise single actuator

## Switch Actuator Indexing Position Quantity:

2 single actuator

#### **Terminal Type:**

Tab w/screw

#### **Switch Actuator Positioning Increment:**

90.0 degrees single actuator

## **Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level

#### Style Designator:

Tap, circuit selector

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5930-00-420-7433

Rotary Switch - Page 2 of 2

# Demilitarization:

Yes - demil/mli

Fiig:

A052b0

