# NSN 5930-00-420-7526 Rotary Switch - Page 1 of 2



Rolary Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-00-420-7526
Thread Class:
2a single mounting facility
Thread Length:
0.375 inches single mounting facility
Overall Length:
4.290 inches
Overall Height:
1.000 inches
Overall Width:
0.940 inches
Shaft Diameter:
0.248 inches single actuator and 0.251 inches single actuator
Shaft Length:
0.375 inches single actuator
Nonturn Device Radius:
0.375 inches at 3: 00 o'clock
Individual Section Quantity:
10
Nonturn Device Type:
Tab at 3: 00 o'clock
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
11 each section rear
Mounting Method:
Threaded bushing single mounting facility
Thread Size:
0.375 inches single mounting facility
Contact Voltage Rating In Volts:
30.0 dc at sea level

### **Switch Actuator Indexing Position Quantity:**

11 single actuator

Shaft Type:

Round single actuator

**Terminal Type:** 

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes each section rear

### **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

## NSN 5930-00-420-7526

Rotary Switch - Page 2 of 2



## **Switch Actuator Stop Device Type:** Fixed-adjustable stops single actuator **Contact Load Current Rating:** 300.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Contact surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A052b0