

View Online at <https://aerobasegroup.com/nsn/5930-00-420-9580>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Height:

0.938 inches

Overall Width:

0.875 inches

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.250 inches single actuator

Nonturn Device Radius:

0.375 inches at 10: 30 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 10: 30 o'clock

Operating Temperature Range:

-25.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

4 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 lowest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

800.0 milliamperes resistive load lowest ac voltage rating at sea level

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0