

View Online at <https://aerobasegroup.com/nsn/5930-00-421-0892>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

0.500 inches

**Overall Height:**

1.366 inches

**Overall Width:**

1.750 inches

**Unthreaded Mounting Hole Diameter:**

0.089 inches single mounting facility

**Distance Between Mounting Facility Centers:**

1.178 inches single mounting facility

**Individual Section Quantity:**

1

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Actuator Type:**

Thumbwheel single actuator

**Features Provided:**

Rfi shielding

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 single section

**Contact Arrangement Truth Table:**

Bcd, 1 pole - 10 positions single section

**Color:**

White single indicator marking

**Precious Material And Location:**

Stator contact surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0