

View Online at <https://aerobasegroup.com/nsn/5930-00-421-0892>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

0.500 inches

Overall Height:

1.366 inches

Overall Width:

1.750 inches

Unthreaded Mounting Hole Diameter:

0.089 inches single mounting facility

Distance Between Mounting Facility Centers:

1.178 inches single mounting facility

Individual Section Quantity:

1

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel single actuator

Features Provided:

Rfi shielding

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

10 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 single section

Contact Arrangement Truth Table:

Bcd, 1 pole - 10 positions single section

Color:

White single indicator marking

Precious Material And Location:

Stator contact surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0