

View Online at <https://aerobasegroup.com/nsn/5930-00-421-2789>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Bushing Length:**

Between 0.455 inches and 0.485 inches

**Body Length:**

Between 0.970 inches and 1.030 inches

**Body Width:**

Between 0.500 inches and 0.530 inches

**Body Height:**

Between 0.595 inches and 0.625 inches

**Actuator Diameter:**

Between 0.335 inches and 0.355 inches

**Actuator Height:**

Between 0.230 inches and 0.290 inches

**Maximum Voltage Rating In Volts:**

120.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0