NSN 5930-00-421-8843

Rotary Switch - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-00-421-8843

Thread Class:

2a single mounting facility

Thread Length:

0.292 inches single mounting facility and 0.332 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

Between 2.040 inches and 2.186 inches

First Flat Length:

0.230 inches single actuator and 0.270 inches single actuator

Flat Height:

0.084 inches single actuator and 0.104 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.126 inches single actuator

Shaft Length:

0.832 inches single actuator and 0.912 inches single actuator

Overall Diameter:

Between 0.735 inches and 0.765 inches

Nonturn Device Radius:

0.245 inches at 3: 00 o'clock and 0.275 inches at 3: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 each section front

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

195.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

4 each section

NSN 5930-00-421-8843Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:	
3 single actuator	
Shaft Type:	
Round, flatted single actuator	
Terminal Type:	
Tab, solder lug	
Contact Switching Action:	
Breaks before makes each section rear	
Switch Actuator Positioning Increment:	
30.0 degrees single actuator	
Detent Rotational Torque Range:	
+8.000/+48.000 inch-ounces single actuator	
Switch Actuator Stop Device Type:	
Fixed stop single actuator	
Contact Load Current Rating:	
250.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level	
Style Designator:	
Tap, circular, bushing mount	
Thread Series Designator:	
Unef single mounting facility	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A052b0	