

View Online at <https://aerobasegroup.com/nsn/5930-00-422-0163>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

2.100 inches

Body Diameter:

Between 0.615 inches and 0.650 inches

Bushing Length:

0.420 inches

Body Length:

1.290 inches

Overall Diameter:

0.663 inches

Actuator Style:

Round

Actuator Diameter:

0.446 inches

Actuator Height:

0.270 inches

Actuator Color:

Natural single actuator

Illuminated Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.500 amperes inductive dc and 500.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac and 500.000 milliamperes lamp ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

UNF

Terminal Type And Quantity:

8 tab, solder lug

Specification Data:

81349-mil-s-22885/18 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0