

View Online at <https://aerobasegroup.com/nsn/5930-00-422-0481>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Explosion proof

Body Length:

2.250 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

0.260 inches

Actuator Roller Diameter:

Between 0.370 inches and 0.380 inches

Maximum Voltage Rating In Volts:

110.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.438 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

48.0 ounces

Actuator Movement:

Between 0.010 pretravel inches and 0.250 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Thread Series Designator:

Un

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0