## NSN 5930-00-422-0483

Toggle Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-00-422-0483

| Body Style:  |
|--|
| Bushing mount  |
| Hazardous Locations/environmental Protection:  |
| Weatherproof   |
| Bushing Length:  |
| 0.470 inches   |
| Body Length:   |
| 1.660 inches   |
| Body Width:  |
| 1.340 inches   |
| Body Height:   |
| 1.100 inches   |
| Actuator Style:  |
| Round  |
| Actuator Diameter:   |
| Between 0.420 inches and 0.432 inches  |
| Actuator Height:   |
| Between 1.030 inches and 1.070 inches  |
| Actuator Position-action Relationship:   |
| Up position maintained and down position maintained and center position maintained   |
| Actuator Position-locking Relationship:  |
| Up position no locking action and down position locked out and center position no locking action                                 |
| Maximum Voltage Rating In Volts:   |
| 115.0 ac and 28.0 dc   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Threaded bushing   |
| Features Provided:   |
| Actuator seal  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Thread Size:   |
| 0.469 inches   |
| Contact Load Current Rating At Maximum Rated Voltage:  |
| 20.000 amperes resistive dc and 12.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 15.000 |
| amperes inductive ac and 4.000 amperes lamp ac   |
| Thread Series Designator:  |
| Uns  |
| Terminal Type And Quantity:  |
| 12 screw   |
| Shelf Life:  |

## **NSN 5930-00-422-0483** Toggle Switch - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

Demilitarization:

No

Fiig:

A053a0