## NSN 5930-00-422-0510

Rotary Switch - Page 1 of 2



| ,   |
|---|
| View Online at https://aerobasegroup.com/nsn/5930-00-422-0510 |
| Thread Class:   |
| 2a single mounting facility                                   |
| Thread Length:  |
| 0.468 inches single mounting facility                         |
| Hazardous Locations/environmental Protection:                 |
| Dustproof   |
| Overall Length:   |
| 3.343 inches  |
| First Flat Length:  |
| 0.750 inches single actuator                                  |
| Flat Height:  |
| 0.219 inches single actuator                                  |
| Shaft Diameter:   |
| 0.250 inches single actuator                                  |
| Shaft Length:   |
| 0.969 inches single actuator                                  |
| Overall Diameter:   |
| 2.000 inches  |
| Individual Section Quantity:                                  |
| 3   |
| Knob Manufacturer Code:                                       |
| 82121   |
| Knob Manufacturer Part Number:                                |
| A   |
| Knob Specificationial Markings:                               |
| Arrow   |
| Switch Contact Basic Design:                                  |
| Nonpile-up symmetrical  |
| Pole Quantity:  |
| 1 each section rear   |
| Throw Quantity:   |
| 4 each section rear   |
| Mounting Method:  |
| Threaded bushing single mounting facility                     |

**Features Provided:** 

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

## NSN 5930-00-422-0510

Rotary Switch - Page 2 of 2



## **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round, flatted, threaded hole single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Makes before breaks 3rd section rear **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 5.0 amperes resistive load ac at sea level **Style Designator:** Tap, circular, bushing mount **Thread Series Designator:** Uns single mounting facility Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A052b0