NSN 5930-00-422-3637

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Watertight

Overall Length: 0.780 inches Shaft Diameter:

0.100 inches single actuator



View Online at https://aerobasegroup.com/nsn/5930-00-422-3637

Shaft Length:
0.040 inches single actuator
Overall Diameter:
0.350 inches
Individual Section Quantity:
1
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section rear
Throw Quantity:
4 single section rear
Mounting Method:
Terminal single mounting facility
Features Provided:
Metallic inclosure
Contact Voltage Rating In Volts:
28.0 dc at sea level
Shaft Flat/slot Angular Location:
270.0 degrees from contact position 1 single actuator
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round, slotted single actuator
Terminal Type:
Pin
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
60.0 degrees single actuator
Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level

NSN 5930-00-422-3637

Rotary Switch - Page 2 of 2



Precious Material And Location	ial And Locatio	Α	Material	ious	Pre
--------------------------------	-----------------	---	----------	------	-----

Terminal surfaces gold

Precious Material:

Gold

Style Designator:

Miniature, pin mount

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0