

View Online at <https://aerobasegroup.com/nsn/5930-00-422-5190>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Body Diameter:**

0.562 inches

**Bushing Length:**

0.312 inches

**Body Length:**

0.497 inches

**Actuator Diameter:**

0.375 inches

**Actuator Height:**

0.437 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

**Special Features:**

Adapter marked press to test

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0