

View Online at <https://aerobasegroup.com/nsn/5930-00-422-5190>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Body Diameter:

0.562 inches

Bushing Length:

0.312 inches

Body Length:

0.497 inches

Actuator Diameter:

0.375 inches

Actuator Height:

0.437 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Special Features:

Adapter marked press to test

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0