# NSN 5930-00-425-6244

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-425-6244

#### **Hazardous Locations/environmental Protection:**

Dusttight and humidity resistant and salt spray resistant and shock resistant and vibration resistant

**Overall Length:** 

1.260 inches

**Overall Height:** 

1.695 inches

**Overall Width:** 

1.150 inches

#### **Unthreaded Mounting Hole Diameter:**

0.100 inches single mounting facility

**Individual Section Quantity:** 

4

#### **Longest Horizontal Distance Between Mounting Centers:**

1.090 inches single mounting facility

#### **Longest Vertical Distance Between Mounting Centers:**

0.900 inches single mounting facility

# **Operating Tempurature Range:**

-65.0/+100.0 degrees celsius

### **Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

# **Actuator Type:**

Thumbwheel single actuator

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

# **Mounting Facility Pattern:**

Four position rectangular single mounting facility

### **Switch Actuator Indexing Position Quantity:**

8 single actuator

#### **Terminal Type:**

Wire loop

# **Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

# **Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7 single section

### **Contact Arrangement Truth Table:**

Bcd, 1 pole - 8 positions single section

Color:

White single indicator marking

# **Precious Material And Location:**

Stator surfaces gold

#### **Precious Material:**

Gold

# NSN 5930-00-425-6244

Code Indicating Wheel Switch - Page 2 of 2



Style	Desid	nator:
OLYIC	Deale	mator.

Rectangular inline indicating

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0