

View Online at <https://aerobasegroup.com/nsn/5930-00-425-6982>

**Thread Class:**

2a 1st mounting facility

**Thread Length:**

0.312 inches 1st mounting facility

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

9.812 inches

**Overall Height:**

2.812 inches

**Overall Width:**

2.812 inches

**Unthreaded Mounting Hole Diameter:**

0.201 inches 2nd mounting facility

**Individual Section Quantity:**

15

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

H

**Knob Specification Markings:**

Arr0w

**Longest Horizontal Distance Between Mounting Centers:**

2.296 inches 2nd mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.296 inches 2nd mounting facility

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

15 each section front

**Mounting Method:**

Unthreaded hole 2nd mounting facility

**Features Provided:**

Actuator knob

**Thread Size:**

0.625 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

5.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

16 single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

22.5 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contact and rotor blade surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Test Data Document:**

81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0