

View Online at <https://aerobasegroup.com/nsn/5930-00-425-6982>

Thread Class:

2a 1st mounting facility

Thread Length:

0.312 inches 1st mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

9.812 inches

Overall Height:

2.812 inches

Overall Width:

2.812 inches

Unthreaded Mounting Hole Diameter:

0.201 inches 2nd mounting facility

Individual Section Quantity:

15

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

H

Knob Specification Markings:

Arr0w

Longest Horizontal Distance Between Mounting Centers:

2.296 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

2.296 inches 2nd mounting facility

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

15 each section front

Mounting Method:

Unthreaded hole 2nd mounting facility

Features Provided:

Actuator knob

Thread Size:

0.625 inches 1st mounting facility

Contact Voltage Rating In Volts:

5.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

16 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Precious Material And Location:

Contact and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0