

View Online at <https://aerobasegroup.com/nsn/5930-00-426-2280>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

2.438 inches

Shaft Diameter:

0.265 inches 1st actuator

Shaft Length:

0.875 inches 2nd actuator

Overall Diameter:

1.500 inches

Nonturn Device Radius:

0.438 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 1st actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees 1st actuator

Switch Actuator Stop Device Type:

Fixed stop 1st actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Contact surfaces and rotor silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0