## NSN 5930-00-426-2609

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-426-2609

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.360 inches single mounting facility and 0.390 inches single mounting facility

**Overall Length:** 

Between 1.845 inches and 1.905 inches

**Overall Height:** 

Between 1.250 inches and 1.374 inches

**Overall Width:** 

Between 1.094 inches and 1.156 inches

**Shaft Diameter:** 

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:** 

0.735 inches single actuator and 0.765 inches single actuator

**Nonturn Device Radius:** 

0.521 inches at 3: 00 o'clock and 0.541 inches at 3: 00 o'clock

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Operating Tempurature Range:** 

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 single section rear

**Throw Quantity:** 

4 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section rear

# NSN 5930-00-426-2609

Rotary Switch - Page 2 of 2



Switch	Actuator	<b>Positioning</b>	Increment:
J ** 1 L C 1 1	Actuator	i ositioiiiig	more chierri.

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

### **Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

#### **Test Data Document:**

81349-mil-s-3786/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A052b0