

View Online at <https://aerobasegroup.com/nsn/5930-00-426-2796>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Weatherproof

Body Diameter:

1.500 inches

Bushing Length:

Between 0.970 inches and 1.030 inches

Body Length:

1.115 inches

Actuator Style:

Round

Actuator Diameter:

0.150 inches

Actuator Height:

0.200 inches

Actuator Free Position Height:

Between 0.345 inches and 0.405 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

240.0 ounces

Switch Actuating Force:

Between 272.0 ounces and 368.0 ounces

Actuator Movement:

0.055 pretravel inches and 0.040 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

1 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0