

View Online at <https://aerobasegroup.com/nsn/5930-00-426-5618>

Overall Length:

1.220 inches

Overall Height:

0.460 inches

Body Diameter:

0.620 inches

Body Height:

0.310 inches

Distance Between Mounting Facility Centers:

Between 0.922 inches and 0.952 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

3.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

200.00 actuation point degrees fahrenheit and 196.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Style Designator:

Disc w/flange

Test Data Document:

96906-mil-std-202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0