NSN 5930-00-427-0788

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-427-0788

Individual Section Quantity:
2
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section rear
Throw Quantity:
1 each section rear
Mounting Method: Threaded husbing w/papel and single mounting facility.
Threaded bushing w/panel seal single mounting facility Contact Voltage Pating In Voltage
Contact Voltage Rating In Volts:
500.0 dc at sea level
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab adder luc
Tab, solder lug
Switch Actuator Positioning Increment:
Switch Actuator Positioning Increment: 30.0 degrees single actuator
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type:
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating:
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 300.0 milliamperes resistive load ac at sea level
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 300.0 milliamperes resistive load ac at sea level Style Designator:
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 300.0 milliamperes resistive load ac at sea level Style Designator: Tap, circular, bushing mount
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 300.0 milliamperes resistive load ac at sea level Style Designator: Tap, circular, bushing mount Shelf Life:
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 300.0 milliamperes resistive load ac at sea level Style Designator: Tap, circular, bushing mount Shelf Life: N/a
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 300.0 milliamperes resistive load ac at sea level Style Designator: Tap, circular, bushing mount Shelf Life:
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 300.0 milliamperes resistive load ac at sea level Style Designator: Tap, circular, bushing mount Shelf Life: N/a
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 300.0 milliamperes resistive load ac at sea level Style Designator: Tap, circular, bushing mount Shelf Life: N/a Unit Of Measure: Demilitarization:
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 300.0 milliamperes resistive load ac at sea level Style Designator: Tap, circular, bushing mount Shelf Life: N/a Unit Of Measure: Demilitarization: No
Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 300.0 milliamperes resistive load ac at sea level Style Designator: Tap, circular, bushing mount Shelf Life: N/a Unit Of Measure: Demilitarization: