

View Online at <https://aerobasegroup.com/nsn/5930-00-428-8931>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.694 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.062 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.062 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded hole 2nd mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Special Features:

Dent action between 0 and 180 degspring return from 270 to 180 degrees terminals 1 5 6 and 10 are make before break. Terminals 4 and 9 are special cut - make before break from 180 to 270 degrees only

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0