

View Online at <https://aerobasegroup.com/nsn/5930-00-428-8931>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

4.694 inches

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

1.062 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.062 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Threaded hole 2nd mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load dc at sea level

**Special Features:**

Dent action between 0 and 180 degspring return from 270 to 180 degrees terminals 1 5 6 and 10 are make before break. Terminals 4 and 9 are special cut - make before break from 180 to 270 degrees only

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0