

View Online at <https://aerobasegroup.com/nsn/5930-00-429-0238>

**Hazardous Locations/environmental Protection:**

Dusttight

**Overall Length:**

5.000 inches

**Overall Height:**

4.125 inches

**Unthreaded Mounting Hole Diameter:**

0.204 inches

**Distance Between Mounting Facility Centers:**

4.750 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -50.0 degrees fahrenheit and 167.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

27 single pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.125 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

4.20 actuation point inches of water and 3.80 deactuation point inches of water and 0.20 differential point inches of water

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Special Features:**

Cannon connector

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0